


WT plug

Right angle plug, cable collet fix the cable. With inner components to avoid cables moving, and sleeve to prevent the cable from bending.

Series	Style	Dimension					
		A	L	M	H	S1	S2
0S	WT	13	23	13	25.3	8	6.5
1S	WT	16	26.5	15.5	28.8	10	8.5
2S	WT	20	31	19	37	13	11

Numbering rules:



For example:

Straight plug with sleeve

1SHT00650N: 1S Series straight plug, multi- contact of 6 pins, apply to cable diameter of 5.0mm, cable collet fix with black sleeve.

Fixed receptacle

2SSZ008: 2S Series fixed receptacle, fixed with two nuts, without key, multi- contact of 8 pins. Omit the later code or replaced by 0000.

Fixed coupler plug

1SHZ00450N: 1S Series coupler plug, without key, multi- contact of 4 pins, apply to cable diameter of 5.0mm, cable collet fix with black sleeve.

S Series connector with the following main features:

1. Security of the push-pull self-latching system;
2. multi-core type(2-6)
3. Solder or PCB contacts (straight and elbow);
4. high-density installation for saving space ;
5. high-low insulator positioning avoid mismathing;
6. 360 degree screening for full EMC shielding;

Parts of connector:

1. shell made of copper alloy, stainless steel is used in special occasions, plated with Nickel or Chrome;
2. pin and jack made of copper alloy, plated with gold;
3. insulator molded with engineering plastic which is high-temperature endurable and good insulating;
4. sleeve molded with soft plastic to protect cables.