

# PN...SV coupler plugs - PN...PV coupler socket-outlets, for entertainment



- PN...SV types 16A (IP44), entry with cable gland colour RAL 9005 black, enclosure colour RAL 9005 black
- PN...PV types 16A (IP44), enclosure and spring lid colour RAL 9005 black, entry with cable gland
- Compliant with EN 60309-1 and -2
- PN...SV types, enclosure and insert in insulating, thermoplastic, self-extinguishing material
- PN...PV types, enclosure, insert and spring lid in insulating, thermoplastic, self-extinguishing material
- Terminals with retained screws
- IP44 degree of protection (EN 60529)

**16A coupler plugs**  
**IP44 degree of protection**  
**low voltage:**  
**from over 50V up to 690V**



**NEW**

**16A coupler socket-outlets**  
**IP44 degree of protection**  
**low voltage:**  
**from over 50V up to 690V**




**NEW**

Number of poles	Frequency Hz	Voltage V	Earthing contact position h	Part No.	Part No.
2P+⊕	50 and 60	200 - 250	6	PN 1663 SV	PN 1663 PV
3P+⊕	50 and 60	380 - 415	6	PN 1664 SV	PN 1664 PV
3P+N+⊕	50 and 60	200/346 - 240/415	6	PN 1665 SV	PN 1665 PV

dimensions in mm


(16A) PN ... SV



PN...SV	A	B	ø min	ø max
16A 2P+⊕	129	59.5	7	16
3P+⊕	129	67	7	16
3P+N+⊕	129	75	8	24

dimensions in mm

(16A) PN ... PV



PN...PV	A	B	ø min	ø max
16A 2P+⊕	146	74.5	7	16
3P+⊕	146	84.5	7	16
3P+N+⊕	146	92.5	8	24

dimensions shown are not binding  
 and may be changed without notice